

AirShot2

02A100010



The compact pressured air cleaning system AirShot2 works with pressured air pulses instead of a continuous air flow, thus reducing the required amount of air significantly and enabling a very compact design.

Furthermore the pressure pulses perform a more effective cleaning than continuous air flow systems, making the AirShot2 a valuable addition to every system.

AirShot2 can be used as an alternative to a standard compressor and can be operated with a TriBox3. To prevent the AirShot2 from overheating it features a internal temperate monitor which indicates excessive heat with a LED.

The cleaning process of the AirShot2 requires only 10 seconds. It can be triggered at a minimum interval of 5 minutes.

Technical specifications

ENERGY SUPPLY

Voltage supply	230 V Version	230 VAC, max. 200 W, 0,86 A
	110 V Version	110 VAC, max. 200 W, 1,8 A

INTERFACES

Connection	for 6 mm hoses (4 mm inner diameter)
Power cable length	3 m
Control line length	5 m
Trigger Input	12...24 VDC, M8 4-Pin
Wiper Output	M8 4-Pin

DISPLAY

LED	3 x Status LED
------------	----------------

AMBIENT

Temperature Impulse Box	-5...+40 °C
Temperature Compressor	-10...+40 °C
Protection type	IP44

MECHANICS

Size w/h/d	190 x 260 x 125 mm and 90 x Ø46 mm
Weight	4.4 kg
Housing	Polycarbonate

SETTINGS

Standard	10 s every 5 min
Max. Pressure	7 bar