



VIPER

17SXXXXX0



VIPER measures the spectrally resolved light attenuation in the wavelength range from 360 to 720 nm and thus enables the simultaneous, precise determination of several parameters. Five selected, energy-saving LEDs serve as the light source and ensure stable measurement results and a long service life.

The sensor is available in various path lengths as well as in stainless steel and titanium versions, allowing it to be used flexibly in a wide variety of media - for example for water monitoring, color measurement of aqueous solutions or for quality control of drinking water.

Like all TriOS sensors, VIPER is equipped with nano-coated optical windows that effectively prevent fouling. Additional parameters can be installed subsequently via software if required.

Thanks to the integrated TriOS G2 interface, sensor configuration is particularly easy: it is carried out directly via a web browser. This makes integration into existing process control systems and external data loggers easier than ever before.

The TriOS compressed air flushing is also available for the 100 mm, 150 mm and 250 mm paths!

Advantages

- Without sampling and sample preparation
- Delay-free
- Without reagents
- Optical windows with nano-coating
- LED technology

Applications

- Drinking water monitoring
- Environmental monitoring
- Color measurement
- Quality assurance
- Petrochemistry
- Industrial applications

Technical specifications

Measure- ment tech- nology	Light source	5 LED	
	Detector	High-end miniature spectrometer	
		256 channels	
		360 to 720 nm, 2.2 nm/pixel	
Measuring principle		Attenuation	
Optical path		10 mm, 50 mm, 100 mm, 150 mm, 250 mm	
Parameters		SAK ₄₃₆	
		Pt-Co color number (APHA/Hazen) (390 nm, 455 nm)	
		Coloring based on DIN EN ISO 7887-C (410 nm, 436 nm, 525 nm, 620 nm)	
		Cr-Co color number (380 nm, 413 nm)	
Measuring range		0.01...2.5 AU (absorption units)	
Measuring accuracy		< 0,2 %	
Turbidity compensation		Yes	
Data logger		~ 2 GB	
Response time T100		2 min	
Measuring interval		≥ 1 min	
Housing material		Stainless steel (1.4571/1.4404) or titanium (3.7035)	
Dimensions (L x Ø)		495 mm x 48 mm*	~ 19.5" x 1.9"*
Weight	VA	~ 2.4 kg*	~ 5.3 lbs*
	Ti	~ 1.3 kg*	~ 2.9 lbs*

*with 50 mm path

interface	digital	Ethernet (TCP/IP)
		RS-232 or RS-485 (Modbus RTU)
Power consumption		≤ 3 W

Power supply		12 - 24 VDC ($\pm 10\%$)	
Maintenance effort		≤ 0.5 h/month typical	
Calibration/maintenance interval		24 months	
System compatibility		Modbus RTU	
Warranty		1 year (EU: 2 years)	
Max. Pressure	with SubConn	30 bar	~ 435 psi
	with fixed cable	3 bar	~ 43.5 psi
	in FlowCell	1 bar, 2...4 L/min	~ 14.5 psi, 0.5 to 1.0 gpm
Degree of protection		IP 68	NEMA 6P
Sample temperature		+2...+40 °C	~ +36 to +104 °F
Ambient temperature		+2...+40 °C	~ +36 to +104 °F
Storage temperature		-20...+80 °C	~ -4 to +176 °F
Inflow velocity		0.1...10 m/s	~ 0.33 to 33 fps